

L2 ANSWER 1 OF 1 CA COPYRIGHT 2002 ACS  
AN \*\*\*76:47902\*\*\* CA  
TI Zeolite pellets  
IN Morishita, Toshio; Kazui, Mitsuo; Tsukidate, Takaaki  
PA Tekkosha Co., Ltd.  
SO Jpn. Tokkyo Koho, 2 pp.  
CODEN: JAXXAD  
DT Patent  
LA Japanese  
NCL 15J1  
CC 49 (Industrial Inorganic Chemicals)  
FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	JP 46032572	B4	19710922	JP	19660921
AB	Zeolite powder was mixed with kaolin-type clay and Na (or NH4) hydroxyethyl cellulose, molded, dried, and calcined at 550.degree. for 1 hr to give zeolite pellets with enhanced hardness.				
ST	zeolite pellitization				
IT	Zeolites				
	RL: USES (Uses)				
	(pellets, contg. hydroxyethyl cellulose salts and kaolin)				
IT	Pellets				
	(zeolites, contg. hydroxyethyl cellulose salts and kaolin)				
IT	Cellulose, 2-hydroxyethyl ether, salts				
	RL: USES (Uses)				
	(in zeolite pellets)				